

# HEXAGON HMI SERIES

10.1" Panel PC suitable for ATEX Zone 1/21



## HEXAGON<sup>10.1</sup>

Hexagon series PCL-X-10.1 are industrial Panel PCs with 10.1" display suitable for use in ATEX Zone 1/21.

They are equipped with a capacitive touch screen for user interaction, a capacitive button for equipment power on and a terminal boards for Ex e/Ex i connections and contains last generation Intel® Processors for very low power consumption and very efficient heat dissipation.

PCL-X-10.1 may optionally contain, in "Ex q" enclosure, Bluetooth or Wi-fi radiofrequency modules, whose limits of radiated power and frequency comply with requirements of EN 60079-0.

### TECHNICAL CHARACTERISTICS



Installation Area	ATEX Zone 1/21
Display	10.1" optically bonded to special cover glass
Touch-screen	Industrial grade capacitive touch sensor, capacitive power-on button with LED
Processor	Base: Intel Atom® N3350, RAM: 4 Gb, Hard Disk: 64 Gb Full: Intel Atom® x6425E, RAM: 8 Gb, Hard Disk: 256 Gb
OS	Windows 10® IoT Enterprise LTSC 2019
Connections	Standard: 1x LAN Gb Ex e, 1 x USB Ex e, 1x RS-485 Ex e Available on request: 2 x LAN 10/100Mb Ex e, 2 x USB Ex e, Bluetooth/WiFi module
Integrated Ex i Active Barriers	5 x D.I. channels for non-Ex push buttons (up to SIL3 in dual channel) 2 x D.O. channels for non-Ex (5V, 15mA) LEDs (Simple Apparatus)
ATEX marking	Ex II 2(1) G Ex eb q [ia Ga] IIC T5...T4 Gb Ex II 2(1) D Ex tb [ia Da] IIIC T95°C...T130°C Db IP66
IECEX marking	Ex eb q [ia Ga] IIC T5...T4 Gb Ex tb [ia Da] IIIC T95°C...T130°C Db IP66
Mechanical protection	Rugged design, IP66 according to EN 60079-0, both front and back Suitable for installation without enclosure, inside non-Ex certified enclosures or inside Ex eb / Ex tb certified enclosures
Materials	Anodized aluminum, glass (pharma grade stainless steel frame on request)
Supply Voltage	24Vdc ±10%


Special executions and customizations available on request.

# HEXAGON HMI SERIES

10.1" Panel PC suitable for ATEX Zone 1/21



## MECHANICAL DRAWING



### Panel mounting on Ex eb / Ex tb enclosure

Use of mounting kit with reinforcement back frame allows installation on Ex eb/Ex tb certified cabinets. Installation can be done as well inside a standard non-certified cabinet or free standing.

Nominal window cut-out: 308 x 251.50 (W x H) mm

### Accessories available on request

PCL-X-10.1 can be supplied mounted inside a Stainless Steel AISI304 custom cabinet with integrated handles.

Arm mounting or foot pedestal thanks to symmetric design. Supports RITTAL CP40 stainless steel.

